



ColdCube™ Connect – Containers

Flexible, portable cooling, freezing and heating
– now Bluetooth connected



ColdCube™ Connect – Containers

Flexible Cooling, Freezing and Heating

- Cooling and heating options now available on all models
- Powerful cooling (30°C to -10°C) and freezing (40°C to -24°C)
- Easily adapted to suit different applications
- Runs as standard on 12/24V DC with optional 110-240V AC
- Consistent temperature control for cargo protection
- Digital controller for efficient operation
- Integrated power disconnect to prevent dead battery
- Redesigned interior to maximise load capacity

Bluetooth added for Total Connectivity and Visibility

- Turns your mobile device into a wireless user interface
- Precise temperature set-point control
- Easy viewing of temperature and status without opening container

Built for the Toughest Environments

- One-piece moulded polyethylene design for outstanding durability, strength and lightness
- Components always designed and tested for use in mobile applications
- Food-grade materials used throughout for hygienic operation and easy cleaning
- Simple to move with integrated handles and transport accessory kits

Extended Range fits Every Need

- Five different sizes and sixteen options ensure your business needs are fully satisfied

Potential Applications

- Small vehicles for businesses with limited capacity requirements for cooling and freezing
- Rental units for use wherever portable temperature control is needed
- Load optimisation in larger vans and full size trailers
- Top loader units for sampling or leisure use

Specifications

- 12/24V DC or 110-240V AC* (consumes 9-25 amps at 12V DC)
- Optional AC to DC power rectifier
- Hermetic digital compressor
- High quality insulation up to 130mm thick
- Digital temperature control with readout
- R-134a refrigerant – models 6100249 and 6100250 use R-404A
- CE, TUV and ATP certified
- 2 years warranty on parts



Fully Connected and Portable Heating, Cooling and Freezing solutions for every application

CHOOSE FROM A RANGE OF FREEZING AND COOLING UNITS IN A VARIETY OF SIZES

PART NO.	STYLE	GROSS CAPACITY (L)	MINIMUM TEMP.	MAX POWER (AMPS 12V DC)	REFRIGERATION TYPE	EXTERNAL DIMENSIONS (MM)	INTERNAL DIMENSIONS (MM)	WEIGHT (KG)
6100235	F	32L	> -24°C	9	R-134a	670x390x480	327x223x344	22.5
6100237	F	82L	> -24°C	9	R-134a	940x560x551	523x358x366	35
6100239	C	140L	> -10°C	10	R-134a	1000x620x710	620x369x510	52
6100240	C & H	140L	+30°C to -10°C	10	R-134a	1000x620x710	540x369x510	54
6100241	F	140L	> -21°C	18	R-134a	1000x620x710	590x369x510	55
6100243	C	330L	> +0°C	10	R-134a	1020x1000x1000	810x550x660	80
6100244	C & H	330L	+30°C to +0°C	10	R-134a	1020x1000x1000	730x550x660	83
6100245	F	330L	> -21°C	18	R-134a	1020x1000x1000	780x550x660	83
6100247	C	720L	> +0°C	20	R-134a	1400x1100x1100	1020x850x780	144
6100248	C & H	720L	+30°C to +0°C	20	R-134a	1400x1100x1100	940x850x780	147
6100249	F	720L	> -24°C	32	R-404A	1400x1100x1100	980x850x780	150

Ambient temperature range: -10°C to +50°C

ACCESSORIES

COLD CUBE MODEL	1 SHELF	2 TRANSPORT KITS TROLLEYS	2 TRANSPORT KITS PALLET BASE	3 BLUE-TOOTH MODULE	4 PLASTIC STRIP CURTAIN	5 FIXING KIT/TIE DOWN KIT	6 INTERNAL FAN KIT	7 AC/DC CONVERTER	8 HANDLE LOCK KIT
6100235	Standard wire basket	-	-	401420*	-	-	781977	401421	-
6100237	Standard wire basket	-	-	401420*	-	-	781978	401421	-
6100239	936041 (5 MAX)	6100202	-	401420	6100219	6100206	781979	401421	903950
6100240	936041 (5 MAX)	6100202	-	401420	6100219	6100206	-	401421	903950
6100241	936041 (5 MAX)	6100202	-	401420	Standard	6100206	781979	401422	903950
6100243	936042 (3 MAX)	6100203	6100204	401420	6100220	6100206	781979	401421	903950
6100244	936042 (3 MAX)	6100203	6100204	401420	6100220	6100206	-	401421	903950
6100245	936042 (3 MAX)	6100203	6100204	401420	Standard	6100206	781979	401422	903950
6100247	935838 (5 MAX)	-	-	401420	Standard	903951**	781980	401422	-
6100248	935838 (5 MAX)	-	-	401420	Standard	903951**	-	401422	-
6100249	935838 (5 MAX)	-	-	401420	Standard	903951**	781980	401423	-

*Bluetooth interface 423382 needed additionally to connect to AC power source

** With pallet base removed

Accessories

We offer a wide range of accessories to cater for different applications.

1 SHELF

- Adjustable to suit the contents of your load
- 30 kg capacity per shelf
 - Available for all sizes except top loaders
 - Can support Gastronorm Boxes

2 TRANSPORT KITS

- Trolley**
- Provides ease of mobility
 - Available for 140L and 330L units

Pallet Base

- Allows for easier loading into truck or van
- Available for 330L unit

3 BLUETOOTH MODULE

- Load temperature conveniently monitored on your mobile device
- Available for all units

4 PLASTIC STRIP CURTAIN

- Reduce cold air leakage when door is open
- Available for the 140L and 330L cooling units (standard on 140L, 330L and 720L freezing unit)

5 FIXING KIT

- Easily secures unit to vehicle floor
- Available for all units except 82L

6 INTERNAL FAN KIT

- Ensures optimal ventilation inside the ColdCube for load protection
- Available for all 32L, 82L and all 140L, 330L and 720L Cooling and Freezing only (standard for heating units)

7 AC/DC CONVERTER

- Optional AC/DC converter to connect the ColdCube to a AC power source

8 HANDLE LOCK KIT

- Handle Lock Kit to stack ColdCubes





europe.thermoking.com



For further information, please contact:



Thermo King is a brand of Ingersoll Rand®. Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands — including Ingersoll Rand®, Thermo King®, Trane® and Club Car® — work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a global business committed to a world of sustainable progress and enduring results.



ingersollrand.com

Ingersoll Rand - Lenneke Marelaan 6, B-1932 Sint-Stevens-Woluwe, Belgium.

© 2018 Ingersoll-Rand Company Limited TK 70001 (02-2018)-EN4